

CLAIMS

WHAT IS CLAIMED IS:

1. A method for manufacturing a clip, comprising:

providing a sheet of material defining a plane;

5 removing one or more portions from the sheet to provide a clip comprising a generally-annular body including a plurality of looped elements defining a periphery, and a plurality of tines extending from the body within the plane; and

deforming the clip to a transverse configuration, wherein  
10 the tines extend out of the plane.

2. The method of claim 1, wherein the sheet comprises a nickel-titanium alloy.

15 3. The method of claim 1, further comprising coating at least a portion of the clip with a therapeutic coating.

4. The method of claim 1, further comprising creating a radiopaque marker on at least a portion of the clip.

20

5. The method of claim 1, wherein deforming of the clip to the transverse configuration comprises loading the clip onto a delivery apparatus.

6. The method of claim 1, further comprising heat treating the clip with the tines extending within the plane to program a shape memory of the sheet of material before deforming of the  
5 clip to the transverse configuration.

7. The method of claim 1, further comprising compressing the looped elements to a compressed state to reduce a periphery of the clip.

10

8. The method of claim 1, wherein the looped elements are compressed when the clip is deformed to the transverse configuration.

15

9. The method of claim 1, further comprising coating at least a portion of the clip with a hydrophilic polymer.